

Spijkstaal

SPIJKSTAAL 302-304-304P

The Spijkstaal 302 and 304 offer towing capacities of 2,000 kg and 4,000 kg respectively, making them versatile for various transport tasks. Both models are equipped with a powerful electric motor for reliable performance. Thanks to their compact design and excellent maneuverability, the 302 and 304 are well suited for use on internal business premises and for various facility services.

302-304-304P

DRIVE/BATTERY	302	304	304P	
Asynchrone AC motor	1.2	2.6	2.6	kW
Battery voltage	24	24	24	V
Battery capacity	300	300	300	Ah
Transmission	1:30	1:19	1:19	
PERFORMANCE				
Max. speed	9	14	14	km/h
Pull capacity	2.000	4.000	4.000	kg
Max. drawbar pull	1.250	2.750	2.750	N
WEIGHTS				
Service weight (incl. batt.)	540	629	655	kg
DIMENSIONS				
Lenght	1.739	1.739	2.026	mm
Width	750	750	750	mm
Track width rear	-	650	650	mm
Wheelbase	650	650	650	mm
Ground clearance, center of wheelbase	100	100	100	mm
Turning radius	1.685	1.685	1.685	mm
TYRES/SUSPENSION				
Tyre size, front	300*75	300*75	300*75	
Tyre size, rear	160*50(2)	200*50(4)	200*50(4)	
Suspension front	Rigid	Rigid	Rigid	
BRAKES				
Service brake	Hydraulic operated disc brake			
Parking brake	Electromagnetic brake			
OPTIONS E.G.				
Battery exchange system	Bluespot		Cabin	
Flash light	Various trailer couplings			

Scan and view this vehicle online